



STANDARD SCOPE OF SUPPLY

Diesel Engine; Engine with direct injection, water cooled engine, 4 stroke, rated at 1500 RPM, conforming to ISO 3046 / BS 5514 has the following specifications:

- Mechanical governor /Electronic Governor (Optional)
- Turbocharge and aftercooler, pulse tuned exhaust manifold, stainless steel exhaust flexible connection
- Radiator Cooled, turbo charged after cooled
- Plate type, lube oil, cooler
- Filters-fuel, lube oil
- Dry type replaceable paper element air cleaner
- Flywheel housing and flywheel to suit single bearing alternator
- Starting motor
- Electric, battery charging alternator
- First fill lube oil and coolant

Alternator; Flexible disc, Close coupled

- Brushless alternator
- Self-excited, self-regulated
- Class 'H' insulation limited to temperature rise of class H
- Salient pole revolving field
- Single bearing
- AVR - Automatic voltage regulator

Canopy; Modular type, sound isolation cabinet

- Base rail with draw-out type fuel tank is provided with a drain plug, air Vent, inlet and outlet connections, level indicator, manhole etc.
- Sub-base fuel tank with 8 hours capacity at 100% load.
- 12V dry, batteries with connecting leads and terminals
- Custom color application



Diesel Engine

1500 RPM / 50 Hz.

230/400 VAC - 3 Phase - Cos ϕ 0,8

Auto / Manuel – Open / Canopied Type

Customizable design according to your request...

GENERATOR SPECIFICATIONS

Manufacturer	Turqpower Generator
Model	TP – DD 825
Production Place	Turkey
Stand by Power (kVA / kW)	825 / 660
Prime by Power (kVA / kW)	750 / 600

ENGINE SPECIFICATIONS

Manufacturer	Doosan
Model	DP222LC
No. of Cylinders & Type	12 & Vee
Displacement (lt)	21,927
Bore & Stroke (mm)	128 x 142
RPM	1500
Air Filter Type	Dry
Cooling Method	Water

ENGINE ELECTRICAL SYSTEM

Charging Alt. Voltage (VDC)	24
Starter Voltage (VDC)	24

FUEL SYSTEM

Fuel Type	Diesel
Fuel Tank Capacity (lt)	1050
Fuel Consumption (lt/h)	161,1

LUBRICATING SYSTEM

Lubricating capacity (lt)	40,0
Grade	15W40 API CI4
Change Periods (hours)	250

COOLING SYSTEM

Cooling Capacity (lt)	114,0
Max. Ambient Temp. (°C)	50
Change Periods (hours)	250

ALTERNATOR SPECIFICATIONS

Voltage (VAC)	230 / 400
Frequency (Hz)	50
Type	4 Pole
Cos ϕ	0,8
Insulation	H
Protection Class	IP23
Bearing	Single
Coupling	Flexible Disc

CONTROLLER SYSTEM

Manufacturer	Datakom
Model	D300 MK2
Production Place	Turkey
Language	English (to be customized)
Display	128x64 graphical LCD
Security	3 level configuration password
Communication	USB – J1939 - CANBUS
IP Protection	IP65



DIMENSIONS

OPEN TYPE	
Length (mm)	4000
Width (mm)	1700
Height (mm)	2700
Weight (kg)	4400

DIMENSIONS

WITH CANOPY TYPE	
Length (mm)	4900
Width (mm)	1700
Height (mm)	2700
Weight (kg)	5700

*Turqpower Generator reserves the right to make change in the model, technical spect, equipment and accessories without prior notice

**Updated January 2021