



## STANDARD SCOPE OF SUPPLY

**Diesel Engine; Engine with direct injection, water cooled engine, 4 stroke, rated at 1500 RPM, conforming to ISO 3046 / BS 5514 has the following specifications:**

- Mechanical governor /Electronic Governor (Optional)
- Turbocharger, pulse tuned exhaust manifold, stainless steel exhaust flexible connection
- Radiator Cooled
- Plate type, lube oil, cooler
- Filters-fuel, lube oil
- Dry type replaceable paper element air cleaner
- Flywheel housing and flywheel to suit single bearing alternator
- Starting motor
- Electric, battery charging alternator
- First fill lube oil and coolant

## Alternator; Flexible disc, Close coupled

- Brushless alternator
- Self-excited, self-regulated
- Class 'H' insulation limited to temperature rise of class H
- Salient pole revolving field
- Single bearing
- AVR - Automatic voltage regulator

## Canopy; Modular type, sound isolation cabinet

- Base rail with draw-out type fuel tank is provided with a drain plug, air Vent, inlet and outlet connections, level indicator, manhole etc.
- Sub-base fuel tank with 8 hours capacity at 100% load.
- 12V dry, batteries with connecting leads and terminals
- Custom color application



**Diesel Engine**

**1500 RPM / 50 Hz.**

**230/400 VAC - 3 Phase - Cos  $\phi$  0,8**

**Auto / Manuel - Open / Canopied Type**

**Customizable design according to your request...**

## GENERATOR SPECIFICATIONS

Manufacturer	Turqpower Generator
Model	TP - I 220
Production Place	Turkey
Stand by Power (kVA / kW)	220 / 176
Prime by Power (kVA / kW)	200 / 160

## ENGINE SPECIFICATIONS

Manufacturer	FPT Iveco
Model	N67TM7
No. of Cylinders & Type	6 & Line
Displacement (lt)	6,7
Bore & Stroke (mm)	104 x 132
RPM	1500
Air Filter Type	Dry
Cooling Method	Water

## ENGINE ELECTRICAL SYSTEM

Charging Alt. Voltage (VDC)	12
Starter Voltage (VDC)	12

## FUEL SYSTEM

Fuel Type	Diesel
Fuel Tank Capacity (lt)	390
Fuel Consumption (lt/h)	42,0

## LUBRICATING SYSTEM

Lubricating capacity (lt)	20,0
Grade	15W40 API CI4
Change Periods (hours)	250

## COOLING SYSTEM

Cooling Capacity (lt)	25,5
Max. Ambient Temp. (°C)	50
Change Periods (hours)	250

## ALTERNATOR SPECIFICATIONS

Voltage (VAC)	230 / 400
Frequency (Hz)	50
Type	4 Pole
Cos $\phi$	0,8
Insulation	H
Protection Class	IP23
Bearing	Single
Coupling	Flexible Disc

## CONTROLLER SYSTEM

Manufacturer	Datakom
Model	D300 MK2
Production Place	Turkey
Language	English (to be customized)
Display	128x64 graphical LCD
Security	3 level configuration password
Communication	USB - J1939 - CANBUS
IP Protection	IP65



## DIMENSIONS

OPEN TYPE	
Length (mm)	2350
Width (mm)	1000
Height (mm)	1600
Weight (kg)	1725

## DIMENSIONS

WITH CANOPY TYPE	
Length (mm)	3250
Width (mm)	1000
Height (mm)	1750
Weight (kg)	2100

\*Turqpower Generator reserves the right to make change in the model, technical spect, equipment and accessories without prior notice

\*\*Updated January 2021